Yealink



YEALINK NETWORK TECHNOLOGY CO., LTD. Email: sales@vealink.com | Web: www.vealink.com

2021-05-HJCP-YW-V2.2



Yealink Desktop IP Phone Solution Product Guide



Contents

| About Yealink | 01 |
|--|----|
| Yealink Communication Solutions | 08 |
| Yealink Audio Conferencing Solution | 15 |
| Yealink T5 Business Phone Series | 27 |
| Yealink T4U Upgraded Business phone series | 39 |
| Yealink T3 Classic Business phone series | 43 |
| Yealink DECT Wireless IP Phone Solution | 47 |
| Yealink USB Peripheral Conferencing Solution | 51 |
| Yealink Management Cloud Service | 57 |
| Yealink IP Phone Accessories | 61 |

About Yealink

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

Frost & Sullivan research confirms that Yealink's leadership position in the IP and SIP desktop phone market is proven by its effective growth strategy, sustainable above-market growth, price/performance value, excellent customer service experience and strong brand equity. Yealink is well positioned to leverage its strength for further success in the enterprise IP desktop phone market.

By Frost and Sullivan





Ecosystem

Yealink's partnership and broad compatibility with major platforms and service providers enable customers to benefit from seamless integration, greater flexibility and productivity.

Technology Partners

























Service Provider Partners

















Company Awards







Yealink Ranked Highest in Customer Satisfaction of VoIP Phones



ITSPA Best VoIP CPE



Technology Fast 500 Asia Pacific



TMC Communications Solutions Product of the Year



FUNKSCHAU Reader's Choice Product of the Year Award



TMC Labs Innovation Award



Yealink One-Stop IP Phone Solutions

Yealink offers a broad selection of highly reliable, easy-to-use IP phone endpoint portfolio to effectively address the needs of productive and easy workspace communication and collaboration. Yealink one-stop solution includes conference IP phone, desktop IP phone, DECT IP phone and Yealink Management Cloud Service. Customers can enjoy the convenience of one-stop purchasing, and easier endpoint device management and faster technical support from Yealink.



| Yealink Desktop IP Phone Use Case | | | | | | |
|--|------|------|------|----------------------------|---------------------------|------|
| | T31P | T31G | T33G | T43U | T46U | T48U |
| Call Load | | | | | | |
| Occasional Use | 1 | √ | | | | |
| Moderate Call Load | | | J | | | |
| Busy Call Load | | | | J | √ | √ |
| Use Case | | | | | | |
| Reception Desk/ Adminstrative Staff | J | J | J | | | |
| Knowledge Worker | | | | | | √ |
| Sales/Marketing | J | J | J | J | J | |
| Manager/Executives/ C-Levels | | | | | | J |
| In-room Mobile Workers | V | J | J | J | J | J |
| Lobby | √ | √ | J | | | |
| HD Video Collaboration | | | | | | |
| Vertical Market | | | | | | |
| Call Center | | | | J | 1 | |
| Government | | | J | J | J | |
| Law Firm | | | J | V | J | |
| Financing Agency | | | J | V | J | |
| Hospitality Guest Room | | | J | | | |
| School Class Room | | | J | | | |
| School Aministrative Office | | | | | | J |
| Features | | | | | | |
| Bluetooth | | | | √ via Yealink BT41 | √ via Yealink BT41 | J |
| Wifi | | | | √ via Yealink WF40/WF50 | √ viaYealink WF40/WF50 | V |
| High-Resolution Color Display | | | | | 1 | √ |
| Gigabit Support | | J | J | J | J | J |

| Yealink Desktop IP Phone Use Case | | | | | | | |
|--|----------------------------|------|------|------|------|------------------------|------|
| | T53 | T53W | T54W | T57W | T58A | T58A with camera | VP59 |
| Call Load | | | | | | | |
| Occasional Use | | | | | | | |
| Moderate Call Load | | | | | | | |
| Busy Call Load | V | 1 | J | J | J | J | J |
| Use Case | | | | | | | |
| Reception Desk/ Adminstrative Staff | | | | | | | |
| Knowledge Worker | | | | J | J | J | J |
| Sales/Marketing | J | 1 | J | | | | |
| Manager/Executives/ C-Levels | | | | J | J | J | J |
| In-room Mobile Workers | J | 1 | V | J | J | J | √ |
| Lobby | | | | | | | |
| HD Video Collaboration | | | | | | J | J |
| Vertical Market | | | | | | | |
| Call Center | J | J | J | | | | |
| Government | J | 1 | V | | | | |
| Law Firm | J | 1 | V | | | | |
| Financing Agency | J | 1 | J | | | | |
| Hospitality Guest Room | | | | | | | |
| School Class Room | | | | | | | |
| School Aministrative Office | | | | 1 | V | J | 1 |
| Features | | | | | | | |
| Bluetooth | √ via Yealink BT41 | J | J | J | J | J | J |
| Wifi | √ via Yealink WF40/WF50 | J | J | J | J | J | J |
| High-Resolution Color Display | | | √ | 1 | J | J | √ |
| Gigabit Support | J | 1 | J | J | J | √ . | J |



Audio Conferencing Solutions

Medium Level





Wireless Conferencing





High Level





CPW90 (Wireless Expansion Microphone)



CPW90 (Wired Expansion Microphone)





Personal Desktop Collaboration

Video Desktop Collaborations







Cordless DECT Communications













13

Personal Desktop Communication

High Level





Entry Level









Medium Level









Audio Conferencing Solution

Conferencing is a rapidly growing market while efficient communication and collaboration is critical to business success. The number of units sold within the tabletop conferencing market is predicted to grow 11.4% and the VoIP segment is expected to growth 10.7% annually, according to 2019 Frost & Sullivan report.

Yealink designs its audio conferencing solution to suit range of different meeting environments. The CP960, the CP920 and the CP930W address today's audio conferencing challenges and unify a clear-and easy conferencing communication experience for both in-room and remote participants.

Yealink Conference Phones offer:

- Different product choices, wired and wireless, to meet the needs of different conference environments
- · Premium HD audio quality for clear communication
- · Yealink Noise Proof to eliminate background noise for a better conversation experience
- · 20-foot microphone pickup for meetings of all sizes
- · Intuitive design for easy and comfortable conferencing operation. Reduce mistakes and improve productivity
- · Bridge calls from different devices into a Yealink Hybrid UC Meeting
- Seamless integration with major UC platforms such as 3CX, BroadSoft, Centile, Metaswitch, Microsoft, Starface

Yealink CP960

First-class, high performance device for mid-large meeting rooms with up to 20 people



Unique Features:

- · 5-inch color touch screen, modern metallic sliver-grey look
- · Yealink Pentagon Meeting Room for comfortable and easy conferencing management
- Available for a pair of the Yealink CPW90 Wireless Microphone to extend coverage and mobility
- · Support for Star Connection with up to 3 Yealink CP960 models for large meeting HD broadcast and voice pickup

Yealink CP920

Cost-effective device for small-to-mid meeting rooms/huddle rooms



Unique Features:

- · Y-shape and modern grey-sliver look with a 3.1-inch 248X120-pixel graphical LCD display
- · Touch-sensitive key pad for easy and comfortable operation
- · Support analog PSTN calls via CPN10 (up to 3 party PSTN)





Yealink CP930W Wireless Conference Phone

Cost-effective device for small-to-mid meeting rooms/huddle rooms

Simply connect the CP930W with the Yealink W60B DECT base, and hold your meeting without need of network or power outlet.



Unique Features:

- \cdot Wireless CAT-iq2.0 DECT technology for premium and stable HD audio quality
- \cdot Yealink Noise Proof for background noise elimination
- · Built-in 3-array microphone for better voice pickup
- · Rechargeable battery for up to 24 hours of talk time

| Yealink Conference Phone Specification | | | |
|--|---|--|--|
| Model | CP960 | | |
| | | | |
| Overview | | | |
| Applications | Medium and large meetings, up to 20 people | | |
| Operating System | Android | | |
| Interface | | | |
| LCD | 5" 720 x 1280-pixel capacitive touch screen | | |
| LCD Backlight | √ | | |
| Touch keypad | X | | |
| USB Port (2.0 compliant) | 2 | | |
| USB 2.0 Micro-B Device Port | 1 | | |
| Ethernet Port | 10/100Mbps | | |
| Wired MIC | 2 (Optional) | | |
| Wireless MIC | 2 (Optional) | | |
| 3.5 mm Jack | 1 | | |
| RJ11 for Mobile Phone | X | | |
| Security Slot | √ | | |
| Audio Features | | | |
| HD Voice | √ . | | |
| Wide-band Codec | G.722, G722.1C, Opus | | |
| Narrow-band Codec | G.711(A/µ), G726, G729, G723, iLBC | | |
| Built-in 3-microphone Array | √ | | |
| Microphone Pickup | 20ft | | |
| Yealink Noise Proof Technology | √ | | |
| Noise Suppression | √ . | | |
| Connectivity | | | |
| Built-in PoE | IEEE 802.3af | | |
| Built-in Bluetooth | Bluetooth 4.0 | | |
| Built-in Wi-Fi | 802.11a/b/g/n/ac | | |
| Battery | X | | |
| Talk Time | X | | |
| Standby Time | X | | |
| Telephony Features | | | |
| Recording | √ . | | |
| Five-way Conferencing | √ . | | |
| Create Meeting Directly | √ . | | |
| Yealink Active Speaker | J | | |
| | | | |

 $\sqrt{}$

Χ

Hybrid UC Meeting

PSTN

| CP920 | CP930W | | | |
|---|---|--|--|--|
| | | | | |
| Over II and madiling madiling on the 45 manufa | On all and madition are allien and to 45 manufactures | | | |
| Small and medium meetings, up to 15 people Linux | Small and medium meetings, up to 15 people RTK-E | | | |
| Linux | KIK-E | | | |
| 3.1" 248 x 120-pixel graphical LCD | 3.1" 248 x 120-pixel graphical LCD | | | |
| √ √ | 5.1 240 X 120-pixel graphical LOD | | | |
| √ √ | √ √ | | | |
| 1 | X | | | |
| X | 1 (Connect to PC) | | | |
| 10/100Mbps | X | | | |
| X | X | | | |
| X | X | | | |
| X | X | | | |
| X | X | | | |
| J | J | | | |
| | | | | |
| √ | √ | | | |
| G.722, G722.1C, Opus | Opus, AMR-WB (optional), G.722 | | | |
| G.711(A/µ), G726, G729, G723, iLBC | PCMU, PCMA, G.726, G.729, iLBC | | | |
| J | J | | | |
| 20ft | 20ft | | | |
| J | J | | | |
| J | J | | | |
| | | | | |
| IEEE 802.3af | X | | | |
| Bluetooth 4.0 | √ (Connect to mobile phone) | | | |
| 802.11b/g/n | X | | | |
| X | Li-ion, 3.6V 7800mAh | | | |
| X | 24h | | | |
| X | 360h | | | |
| , | (At At | | | |
| √ | √ (Via Micro SD card) | | | |
| √ | 1 | | | |
| X | X X | | | |
| X | | | | |
| √ | √ | | | |

√ (Via Yealink CPN10)

Χ



Yealink Innovations Noise Proof Technology

Noise elimination technology is one of the prominent advantages of a conference phone. Collaboration can happen anywhere and anytime but, most of the time, people want a quiet environment to ensure their voice is clearly heard without the interruption or distraction of office machine noises, ringing phones, car horns or a barking dog. Noises make the experience unpleasant and dramatically reduce meeting efficiency.


The Yealink Noise Proof Technology intelligently eliminates background noises. It automatically mutes the microphone when no human speech is detected. When speech is detected, it automatically minimizes background noise.



Yealink Innovations Wireless DECT Microphone

The Yealink CPW90 Wireless Microphone increases voice pickup range and guarantees audio quality. Utilizing Wireless DECT technology, it allows the organization to place the microphone anywhere within the 20-meter signal reception range. This practical accessory adjusts to different types and sizes of conferencing.

- · Optima HD voice, full duplex technology
- · DECT technology
- · Support 20m away from CP960
- · 10-foot/3-meter voice pickup
- · Touch-control mute button
- · 19 hours talk time, 11 days standby time



Yealink Innovations Pentagon Meeting Room

The Yealink Pentagon Meeting Room refers to the Yealink CP960's user interface, which replicates the look of a Pentagon Meeting. This simple and unique interface adds customer value by increasing adoption rates and reducing mistakes.

Key Benefits:

- · Send multiple conference invitations simultaneously
- · Add conference participants without interrupting the ongoing conversation
- · Easily recognize who is speaking with the Active Speaker Display




Yealink Innovations Hybrid UC Meeting

- · The Yealink Hybrid UC Meeting is designed to bridge calls from different devices into one conference call
- · By pairing your device via USB or Bluetooth with your Yealink conference phone, the calls can be connected with the conference phone
- \cdot Tap the merge calls icon to involve all the parties in one call and start your Yealink Hybrid UC Meeting

Extend the Usage


Small to Medium Conference Rooms

Place the Yealink CP960/CP920/CP930W in the middle of the table. The phone supports 20-foot (6-meter) voice pickup.



Lectures, Trainings, Super-large Meetings

Yealink CP960 support Star Connection with up to 3 CP960 units for HD audio broadcasting and pickup in larger situation. Requirement: Deployed in the same subnet.



Large Meeting Rooms/Presentation Sessions

Add a pair of Yealink CPW90 to the CP960. Place the CP960 in the middle and the CPW90 on each side to best catch and deliver the voice.



Analog PSTN Environment

Connect Yealink CP920 to your analog PSTN telephony environment with Yealink CPN10 and PSTN Apapter.



Speakerphone

For HD broadcasting needs, the Yealink conference phone can be a great speakerphone when connecting to a computer via USB or to a mobile phone via Bluetooth. Conversely, you can connect the Yealink CP960 with your PA system using the 3.5mm jack to broadcast the voice from CP960.





Yealink T5 Business Phone Series

Being responsive to changes and demands in the marketplace, Yealink has designed and developed its new T5 Business Phone Series, the most advanced IP desktop phone portfolio in the industry. Leading the way in new personalized collaboration, the Yealink T5 Business Phone Series provides the best possible personalized collaboration experience for businesses of all sizes.

With the Yealink T5 Business Phones, you can help your business benefit from the advanced telephony features, next-generation communication experience and great flexibility, and eventually unleash the power of remote collaboration and maximize the ROI.

Key Features:

- · Video and audio all-inclusive solution for collaborative workspace
- · Yealink Acoustic Shield for distraction-free HD communication
- · Ergonomic design with a high-resolution adjustable display
- · Built-in Wi-Fi, Bluetooth and USB port
- · Illuminated multiple line keys for quick access to common functions
- · Instant content sharing over the phones
- · Corded-cordless phone enabled via a Yealink DD10K DECT dongle
- · Support expansion module Yealink EXP50 (except VP59)



New Personal Collaboration Landscapes

The Yealink T5 Business Phone Series introduces seven phone models for productive desktop communication and collaboration demands. The Yealink Prime Business Phones T53, T53W, T54W and T57W are ideal for highly active voice ommunication users.

The Yealink Smart Business Phones T58A and T58A with Camera, and the Flagship Smart Video Phone VP59 are professional desktop collaboration tools well suited for executive offices and huddle rooms, delivering cutting-edge capabilities and affordable access to professional HD video.







Yealink T5 Smart Business Phones

With remote working becoming ever more prevalent, it is increasingly important to enable easy and smooth collaboration between remote employees and on-campus managers and executives. Yealink Flagship Smart Video Phone VP59, Smart Business Phones T58A and T58A with Camera fulfill the essential needs of professional HD video and voice collaboration at the desk and in small group meetings.

Key Features:

- · Based on Android OS
- · Exceptional HD video collaboration capability
- · Yealink Acoustic Shield and Noise Proof tech-nologies for distraction-free HD communication
- · Full-color touchscreen, fully adjustable for great user experience
- · 27 touch memory keys, 16 SIP accounts
- · Illuminated multiple functions keys for quick access to common features
- · Rich connectivity such as built-in Bluetooth, Wi-Fi and USB port
- · Support expansion module Yealink EXP50 (except VP59)

Yealink T5 Prime Business Phones



Prime Business Phone T53/T53W

- · Entry-level phone, well suited for common workspace
- · 3.7" 360x160-pixel graphical display, fully adjustable
- · 8 line keys, 12 SIP accounts, 21 memory keys
- · USB port integrated for call recording and wireless USB headset



Prime Business Phone T54W

- · Mid-level phone, ideal for professionals and managers with moderate call load
- · 4.3" 480x272-pixel color display, fully adjustable
- · 10 line keys, 16 SIP accounts, 27 memory keys
- · USB port integrated for call recording and wireless headset



Prime Business Phone T57W

- Premium-level phone for executives and busy managers with heavy call load
- · 7" 800x480-pixel color touch display, fully adjustable
- · 29 touch keys, 16 SIP accounts
- · USB port integrated for call recording and wireless headset



Yealink Acoustic Shield Technology

Aiming at delivering distraction-free voice clarity, Yealink Acoustic Shield uses multiple microphones to create a virtual "shield" between the speaker and the outside sound source. Once enabled, it intelligently blocks or mutes sounds from outside the "shield" so that the person on the other end hears you only and follows you clearly.

In busy and noisy workspace such as call centers and office area, Yealink Acoustic Shield technology dramatically reduces frustration and improves productivity.



Adjustable High-Resolution Display


Yealink T5 Business Phone Series has an elegant, ergonomic and user-friendly design which makes navigation and operation easy and enhances productivity. Aligning with a fully adjustable display, the T5 Business Phone Series can easily fulfill the viewing needs at a variety of angles and under a variety of lighting conditions and finally provides optimized user experience.



Corded-cordless Phone System

With the association of the Yealink DECT Dongle DD10K, you are able to expand the T5 Business Phone into a base unit, and make it a corded-cordless phone solution.

- · Connecting with up to 4 Yealink DECT handset units, ideal for SMBs, SOHO
- · Up to 4 concurrent HD voice calls
- · Seamless call switchover between the handset and the desktop phone for greater mobility and flexibility (only when one single wireless handset registered)



Instant Content Sharing

The Yealink T5 Business Phone Series supports instant content sharing with the people on the other end of the call. The speaker can quickly transmit the content over the phone on the call. It helps speed up decision making.

For content sharing, it is required to install Yealink VCD on your computer and bundle your T5 Business Phone with Yealink VCD*.



Intercom System Integration

The Yealink T5 Smart Business Phones VP59, T58A, T58A with Camera can connnect to third party intercom systems for reception applications. Officially certified intercom brands include 2N, Baudisch and Cyberdata.

- · One-touch door opening
- · Visitor viewing
- · Real time small-scale video monitoring over the gate

| Overview Module | VP59 | T58A with Camera |
|--|---|--|
| Overview | VF39 | 136A WIIII Calliela |
| | | |
| Operating System | Android 7.1 | Android 5.1 |
| nterface | | |
| LCD Display | 8" 1280 x 800 pixels capacitive touch screen | 7" 1024X600 pixels capacitive touch screen |
| _CD Type | Adjustable | Adjustable |
| _ED Indicators | 1 | J |
| Memory Keys | 27 touch keys | 27 touch keys |
| JSB Port (2.0 Compliant) | 2 | 2 |
| Ethernet Port | Dual-port Gigabit Ethernet | Dual-port Gigabit Ethernet |
| Handset Port (RJ-9) | 1 | √ |
| Headset Port (RJ-9) | J | J |
| Expansion Module | × | Yealink EXP50 |
| External Yealink AC Adapter (Optional) | AC 100~240V input and DC 12V/1A output | AC 100~240V input and DC 5V/2A output |
| Audio Features | | |
| HD Voice | HD handset, HD speaker | HD handset, HD speaker |
| Speakerphone | Full duplex | Full duplex |
| Videband Codec | G.722,Opus | G.722,Opus |
| Narrowband Codec | G.711(A/µ), G.729A/B, G.726, G.723.1, iLBC | G.711(A/µ), G.729A/B, G.726, G.723.1, iLB0 |
| HAC Handset | √ | √ |
| /ealink Noise Proof | J | √ |
| /ealink Acoustic Shield | J | √ |
| Connectivity | ٧ | V |
| PoE | 1 | √ |
| Bluetooth | v Built-in | v Built-in |
| Vi-Fi | Built-in | Built-in |
| HDMI | J J | X X |
| Foot Stand | √ 1 adjustable angle | 1 adjustable angle |
| Vall Mountable | i adjustable angle | i adjustable arigie |
| Corded-Cordless Phone (Via DD10K) | J | √ |
| Headset | √ USB/Bluetooth/RJ9 | VSB/Bluetooth/RJ9 |
| Camera | 2 mega-pixel (adjustable, plug and play) | 2 mega-pixel (adjustable, plug and play) |
| Jamera /ideo Resolution | 2 mega-pixer (adjustable, plug and play) 1080p@30fps Full-HD | 720p@30fps HD |
| | Н.263, Н.264, Н.264HP, VP8 | 72up@3urps нD H.264, H.264HP, VP8 |
| /ideo Codec | | |
| Ooor Phone Integration | √ / | √ |
| Content Sharing | √ . | √ |
| Telephony Features | - 12 | 10 |
| SIP Account | 16 | 16 |
| 3-Way Video Conferencing | √ | √ |

| Overview | Module | SIP-T53/SIP-T53W |
|--|--------|--|
| Overview | | OII 130/OII 130VV |
| | | T THE STATE OF THE |
| Operating System | | Linux Based |
| Interface | | |
| LCD Display | | 3.7" 360x160 pixels graphical display |
| LCD Type | | Adjustable |
| LED Indicator | | \checkmark |
| Line Key | | 8 |
| Memory Key | | 21 (3 pages, 7 keys per page) |
| USB Port (2.0 Compliant) | | 1 |
| Ethernet Port | | Dual-port Gigabit Ethernet |
| Handset Port (RJ-9) | | \checkmark |
| Headset Port (RJ-9) | | \checkmark |
| Expansion Module | | Yealink EXP50 |
| External Yealink AC Adapter (Optional) | | AC 100~240V input and DC 5V/1.2A output |
| Audio Features | | |
| HD Voice | | HD handset, HD speaker |
| Speakerphone | | Full duplex |
| Wideband Codec | | G.722,Opus |
| Narrowband Codec | | G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC |
| HAC Handset | | 1 |
| Yealink Acoustic Shield | | 1 |
| Connectivity | | |
| PoE | | √ |
| Bluetooth | | Built-in Bluetooth 4.2/T53 via BT40 |
| Wi-Fi | | Built-in (2.4G and 5G)/T53 via WF40/WF50 |
| Foot Stand | | 1 adjustable angle |
| Wall Mountable | | \checkmark |
| Corded-Cordless Phone (Via DD10K) | | √ |
| Headset | | USB/Bluetooth/RJ9 |
| Content Sharing | | √ |
| Telephony Features | | |
| SIP Account | | 12 |
| 3-Way Audio Conferencing | | √ |

| SIP-T54W | SIP-T57W |
|---|---|
| | |
| Linux Based | Linux Based |
| | |
| 4.3" 480x272 pixels color display | 7" 800x480 pixels color display |
| Adjustable | Adjustable |
| √ | √ |
| 10 | 0 |
| 27 (3 pages, 9 keys per page) | 29 touch keys |
| 1 | 1 |
| Dual-port Gigabit Ethernet | Dual-port Gigabit Ethernet |
| J | √ |
| J | √ |
| Yealink EXP50 | Yealink EXP50 |
| AC 100~240V input and DC 5V/2A output | AC 100~240V input and DC 5V/2A output |
| | |
| HD handset, HD speaker | HD handset, HD speaker |
| Full duplex | Full duplex |
| G.722, Opus | G.722, Opus |
| G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC | G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC |
| J | $\sqrt{}$ |
| J | √ |
| | |
| √ | √ |
| Built-in Bluetooth 4.2 | Built-in Bluetooth 4.2 |
| Built-in (2.4G and 5G) | Built-in (2.4G and 5G) |
| 1 adjustable angle | 1 adjustable angle |
| J | \checkmark |
| √ | √ |
| USB/Bluetooth/RJ9 | USB/Bluetooth/RJ9 |
| J | J |
| 16 | 16 |
| J | |



Yealink T4U Series of IP Phones

Experience Modern Voice Communications

The new-gen T4U series greatly improves the calling experience and work efficiency with dual USB ports, Ultra HD sound quality, faster response speed, and even more advanced features. The new T4U series will be a powerful assistant for modern business.

- · Yealink's industry-leading Acoustic Shield Technology & Optima HD audio technology
- · Able to pair two Bluetooth dongles, Wi-Fi dongles, EHS40 headset adapters, USB headsets or USB disks at the same time
- · Equipped with Yealink's new EXP43 expansion module, the new T46U offers a full-color experience
- · 3.7-inch screen and higher resolution
- · Stand with 2 adjustable angles and wall mountable
- · SIP over Transport Layer Security (TLS/SSL)



T43U

- · 3.7-inch large black-and-white screen and the EXP43 support
- · United Yealink Optima HD Voice technology and wideband codec of Opus
- · Flexible buttons that can be easily programmed with 21 paperless DSS keys at most



T46U

- · 4.3" 480 x 272-pixel color display with backlight
- United Yealink Optima HD Voice technology and wideband codec of Opus
- · Flexible buttons that can be easily programmed with 27 paperless DSS keys at most



T48U

- · 7" 800 x 480-pixel color touch screen with backlight United Yealink Optima HD Voice technology and wideband codec of Opus
- · 29 one-touch DSS keys that can be easily programmed to various features
- · 180 additional buttons with a screen-based LCD display and LED system

| Yealink T4U Series of IP Phon | es Specification |
|---------------------------------------|--|
| Model | SIP-T48U |
| | |
| LCD | 7" color touch screen |
| Resolution | 800 x 480 |
| LCD Backlight | √ |
| Line | 16 |
| Line Key | 0 |
| Memory Key | 29 touch keys |
| HD Voice | HD Speaker, HD Handset |
| Wide-band Codecs Narrow-band Codecs | G.722, Opus G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus |
| | G.7 П(А)µ, G.729A/B, G.726,G.725.1, ILBC, Opus |
| N-way Conferencing Ethernet Port | |
| PoE | Dual-port Gigabit Ethernet |
| Handset Port (RJ-9) | √ √ |
| Headset Port (RJ-9) | √ √ |
| USB Port (2.0 compliant) | 2 |
| USB Headset | √ |
| USB Recording | · |
| Yealink Bluetooth Adapter BT40/BT41 | √ |
| Yealink Wi-Fi Adapter WF40/WF50 | · |
| Wireless Headset Adapter | EHS40 |
| Expansion Module | EXP43 |
| Foot Stand | 2 adjustable angles |
| Wall Mounting | , √ |
| External Yealink AC Adapter (optiona) | AC 100~240V input and DC 5V/2A output |
| | I. |

SIP-T46U SIP-T43U





| 4.3" color LCD | 3.7" graphical LCD |
|---|---|
| 480 x 272 | 360 x 160 |
| \checkmark | J |
| 16 | 12 |
| 10 | 8 |
| 27 (3 pages of 9 keys) | 21 (3 pages of 7 keys) |
| HD Speaker, HD Handset | HD Speaker,HD Handset |
| G.722, Opus | G.722,Opus |
| G.711(A/µ), G.729A/B, G.726,G.723.1, iLBC, Opus | G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus |
| 10 | 5 |
| Dual-port Gigabit Ethernet | Dual-port Gigabit Ethernet |
| \checkmark | √ |
| \checkmark | √ |
| \checkmark | √ |
| 2 | 2 |
| √ | √ |
| √ | √ |
| √ | √ |
| √ | √ |
| EHS40 | EHS40 |
| EXP43 | EXP43 |
| 2 adjustable angles | 2 adjustable angles |
| √ | √ |
| AC 100~240V input and DC 5V/2A output | AC 100~240V input and DC 5V/1.2A output |



Yealink Classic Business Phone T3 Series

Facilitate the communication, enrich your business

Yealink new T3 series is a classic and cost-effective entry-level business IP phone for daily desktop voice communications. T3 series maximizes productivity and enhances collaboration for businesses of various scales.

- · Shorter boot time and faster response
- · Industry leading Smart Noise Filtering Technology
- · Superior HD audio performance
- · 5-way local conference function
- · EHS wireless headset integration
- · Yealink Device Management Platform
- · Designed by Yealink original team, T3 series inherits the design concept of Yealink IP phone family



T31P/T31G

- $\cdot\,\text{The T31P}$ and T31G series are fashionable and friendly entry-level gigabit business phone
- · Extra-large 132x64-pixel graphical LCD with backlight
- Built-in Power over Ethernet (PoE) and superb high definition (HD) sound quality



T33G

- · The T33G is high performance business phone
- · Extra-large 320x240-pixel color display with backlight
- · Dual-port Gigabit Ethernet with integrated PoE

| Yealink T3 Series IP Phones Spec | cification |
|--|--|
| Model | T31P/T31G |
| | |
| LCD | 2.3" Graphical LCD |
| Resolution | 132 x 64 |
| LCD Backlight | √ (Adjustable Brightness) |
| Line | 2 |
| Line Key | 2 |
| Memory Key | 2 |
| PoE | √ (T31P/T31G) |
| GigE | √ (T31G) |
| Wireless Headset Adapter | EHS35 |
| N-Way Audio Conferencing | 5 |
| Wide-band Codecs | G.722, Opus |
| Narrow-band Codecs | G.711 (A/µ), G.729AB, G.726, iLBC, G.723.1 |
| Foot Stand | 2 Adjustable Angles |
| Wall Mounting | J |
| Security Slot | √ |
| External Yealink AC Adapter (optional) | AC 100-240V Input and DC 5V/600mA Output |

T33G



| 2.4" Color LCD |
|--|
| 320 x 240 |
| √ (Adjustable Brightness) |
| 4 |
| 4 |
| 12 (4 Pages of 3 Keys) |
| 1 |
| √ (T33G) |
| EHS35 |
| 5 |
| G.722, Opus |
| G.711 (Α/μ), G.729AB, G.726, iLBC, G.723.1 |
| 2 Adjustable Angles |
| 1 |
| 1 |
| AC 100~240V Input and DC 5V/600mA Output |







Wireless DECT Phone Solution

Making phone calls on the move is a vital part of work in various business segments such as warehouses, retails, restaurants, factory sites, SOHOs and SMEs. The Yealink DECT IP Phone Solution is specifically designed to power up your on-the-go business with its sophisticated HD voice, robust battery and 50-meter indoor/300-meter outdoor coverage.

Yealink's comprehensive and sophisticated wireless DECT system comprises multiple phone models. Customers can easily choose the phone that meets their requirements and supports their wireless office.



Yealink DECT Ecosystem

The Yealink W80B DECT IP Multi-Cell System support the networking of one W80DM, the DECT Manager, and up to 30 W80B base stations. This system supports the registration of up to 100 multiple terminal devices, including the W59R, W90B, W53H, W56H, CP930W and DD Phone (T54W + DD10K).

- · Easy setup for users and resellers even in a non-multicast network environment.
- · Seamless roaming and handover solution allowing users to move freely in large spaces.
- · Easy access to multiple phone books.



W60P

- Premium level model catering to frequent on-the-move communications
- · Premium and stable HD audio quality
- · 30 hours of talk time, 16 days of standby time
- · Quick-charge capability
- · 2.4-inch FTF color display for comfortable and productive everyday use
- · Optional water and dust-proof, and drop resistance protective case



W53P

- Reliable and cost-effective choice for moderate -to-active on-the-move communication needs
- · Premium and stable HD audio quality
- · Li-ion battery that supports 18 hours of talk time and 200 hours of standby time
- · Upgraded compact and metallic silver design comfortable to carry and handle
- · 1.8-inch 128x160-pixel LCD display for easy information browsing
- Optional water and dust-proof, and drop resistance protective case



T54W+DD10K

- · Exceptional HD audio quality
- · 2.7-inch graphical LCD display w/ backlight
- · 6 line keys with LED indicator
- · Exceptional HD audio quality
- · 2.7-inch graphical LCD display w/ backlight
- · 6 line keys with LED indicator







Yealink Ruggedized DECT Handset W59R

Yealink W59R, certified to rigorous IP67 standard, is a professional ruggedized DECT handset with integrated Bluetooth and vibration alarm which are pretty eligible for any demanding environment. Besides perfect telephony, this handset is also fully compatible with Yealink W80 Multi-Cell System that provides users with the convenience and good experience of mobile communication in and between each zone. As a reliable and durable handset, its complete alarm functions and integrated G-Sensor lends W59R itself well to the person who works in hazardous locations.

- · HD voice and FNR (Flexible Noise Reduction)
- · 1.8" 128x160 TFT color screen with intuitive user interface
- · 100 phone book memory (store in the base)
- · LC3 (Low Complexity Communication Codec) Plus for high and stable audio quality
- · Rugged DECT handset with IP67 protection rating





CP930W Wireless Conference Phone

Better voice quality, Greater Microphone Pickup

- · Premium HD voice quality powers up face-to-face like pleasant conversations
- · 3-array microphone ensures the voice is captured with clarity
- · Wider microphone pickup range with 20-foot (6-meter) coverage for meetings up to 15 people
- Yealink Noise Proof technology eliminates background noise and delivers quiet communication services

Better Design, More Features:

- · Ergonomic industry design allows to carry with comfort
- · Touch keypad and LED mute indicators for a better user experience
- With Bluetooth and Micro USB port to connect your own device which allows the organizer to either host a Yealink Hybrid UC Meeting (up to 5 parties) or make the phone a super speakerphone

| DECT IP Phone Specificati | on | |
|---------------------------------------|--|--|
| Model | W60P | W53P |
| | | |
| Applications | Premium level for busy call traffic | Mid level for moderate call traffic |
| Display | | |
| LCD Display | 2.4" 240 x 320-pixel TFT color display | 1.8" 128 x 160-pixel TFT color display |
| Handset Size | 175mm x 53mm x 20.3mm | 150mm x 48.4mm x 25mm |
| LCD Backlight | J | J |
| Telephony Features | | |
| Standby Time | 400h | 200h |
| Talk Time | 30h | 18h |
| Battery | Lithium | Lithium |
| Quick Charge | J | √ |
| Headset | 3.5 mm | 3.5 mm |
| Indoor Range/Outdoor Range | 50m/300m | 50m/300m |
| Handset Number Per Base | Up to 8 handsets | Up to 8 handsets |
| SIP Account | 8 | 8 |
| Simultaneous Voice Calls | 8 | 8 |
| Repeater | J | √ |
| DECT Standard | CAT-iq 2.0 | CAT-iq 2.0 |
| Audio Conference | 3-way | 3-way |
| Speed Dial | J | J |
| Audio Features | | |
| Wideband Codec | Opus, AMR-WB (Optional), G.722 | Opus, AMR-WB (Optional), G.722 |
| Narrowband Codec | PCMU, PCMA, G.726, G.729, iLBC | PCMU, PCMA, G.726, G.729, iLBC |
| HD Voice | J | J |
| Connectivity | | |
| Ethernet Interface | 10/100M | 10/100M |
| PoE | J | J |
| Bluetooth | X | х |
| Wall Mountable Base | J | √ |
| Interface | | |
| Softkey | 2 | 2 |
| Navigation Key | 5 | 5 |
| Line Key | X | X |
| Function Key | 6 | 6 |
| Volume Control Key | X | X |
| · · · · · · · · · · · · · · · · · · · | | |


CP930W-Base T54W+DD10K Personal desk Conference room/huddle room 4.3" 480 x 272-pixel color LCD 3.1" 248 x120-pixel graphical LCD 233mm x 222.6mm x 186.1mm x 41.7mm 307.8mm x 298.5mm x 66.9mm Χ 360h 24h Χ Lithium Χ RJ9/USB Χ 50m/300m 50m/300m Up to 8 handsets Up to 8 handsets 8 8 8 8 $\sqrt{}$ 1 CAT-iq 2.0 CAT-iq 2.0 10-way 5-way $\sqrt{}$ $\sqrt{}$ Opus, AMR-WB (Optional), G.722 Opus, AMR-WB (Optional), G.722 $G.711(A/\mu), G.729, G729A, G.726, G.723.1, iLBC$ PCMU, PCMA, G.726, G.729, iLBC $\sqrt{}$ $\sqrt{}$ 10/100M 10/100M $\sqrt{}$ √ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ 4 4 6 3 10 Χ 7 4

2

2

| Tough and reliable with IP67 | standard certified |
|---|--|
| Model | W59R |
| | |
| Key Feature | |
| Design | Ruggedized and robust |
| Protection class | IP67 |
| Simultaneousc voice calls | 2 |
| Bluetooth | √ |
| Vibrate | 1 |
| Standby time | 360h (200hours with Bluetooth headset) |
| Talk time | 28h (18 hours with Bluetooth headset) |
| Battery | 1460mAh Lithium |
| Headset | Bluetooth |
| Indoor range/Outdoor range | 50m/300m |
| DECT standard | CAT-iq2.0 |
| Alarm function | √ |
| 3-way conferencing | √ |
| Speed dial | J |
| OTA | √ . |
| Handset | |
| Size | 157mm x 51mm x 24mm |
| LCD display | 1.8" 128 x 160 TFT colour display |
| LCD backlight | √ |
| Backlit keypad | J |
| Alarm button | J |
| Volume side key | J |
| Audio | |
| Wideband codecs | Opus, AMR-WB (optional), G.722 |
| Narrowband codecs | PCMU, PCMA, G.726, G.729, iLBC |
| FNR (Flexible Noise Reduction) | √ . |
| LC3 (Low Complexity Communication Codec) Plus | √ . |
| HD voice | J |

| System Max. number of bases for system Max. number of handsets for system Simultaneous calls for system Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 30 100 100 8 50m/300m Within group Whole system / H/W56H / CP930W / DD Phone (T41S+DD10K) / Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | W90 DECT IP Multi-Cell System 60 250 250 8 50m/300m Within group Whole system V W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
|---|--|--|
| Max. number of bases for system Max. number of handsets for system Simultaneous calls for system Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 30 100 100 8 50m/300m Within group Whole system √ H/W56H/CP930W/DD Phone (T41S+DD10K) √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 250 250 8 8 50m/300m Within group Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10h √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Max. number of bases for system Max. number of handsets for system Simultaneous calls for system Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 100 100 8 50m/300m Within group Whole system √ H / W56H / CP930W / DD Phone (T41S+DD10K) √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 250 250 8 8 50m/300m Within group Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10h √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Max. number of handsets for system Simultaneous calls for system Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 100 100 8 50m/300m Within group Whole system √ H / W56H / CP930W / DD Phone (T41S+DD10K) √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 250 250 8 8 50m/300m Within group Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10K) ✓ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Simultaneous calls for system Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 100 8 50m/300m Within group Whole system / H/W56H/CP930W/DD Phone (T41S+DD10K) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 250 8 50m/300m Within group Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Simultaneous calls per base Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B W53t OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 8 50m/300m Within group Whole system I / W56H / CP930W / DD Phone (T41S+DD10K) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 8 50m/300m Within group Whole system W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Indoor/outdoor range Handover Roaming Air Synchronization Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | 50m/300m Within group Whole system / H/W56H/CP930W/DD Phone (T41S+DD10K) / Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | 50m/300m Within group Whole system W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Handover Roaming Air Synchronization Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | Within group Whole system V H / W56H / CP930W / DD Phone (T41S+DD10K) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | Within group Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Roaming Air Synchronization Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | Whole system V H / W56H / CP930W / DD Phone (T41S+DD10K) V Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | Whole system √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Air Synchronization Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | √ H / W56H / CP930W / DD Phone (T41S+DD10K) √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | √ W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k) √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Handset module for W80B W53I OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | H/W56H/CP930W/DD Phone (T41S+DD10K) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | W53H/W56H/W59R/CP930W/DD Phone (T41S+DD10k) Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| OTA for handset Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | √ Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Audio Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC | Opus, AMR-WB (optional), G.722 PCMU, PCMA, G.726, G.729, iLBC |
| Wideband codecs Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | PCMU, PCMA, G.726, G.729, iLBC | PCMU, PCMA, G.726, G.729, iLBC |
| Narrowband codecs HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | PCMU, PCMA, G.726, G.729, iLBC | PCMU, PCMA, G.726, G.729, iLBC |
| HD voice Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | | |
| Interface Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | √ | 1 |
| Ethernet interface PoE Wall mountable Features LDAP XML Phonebook | | ٧ |
| PoE Wall mountable Features LDAP XML Phonebook | | |
| Wall mountable Features LDAP XML Phonebook | 10/100M | 10/100M |
| Features LDAP XML Phonebook | J | √ . |
| LDAP XML Phonebook | J | √ . |
| XML Phonebook | | |
| | J | √ |
| | J | √ |
| BroadSoft directory (User & company) | J | √ |
| BroadSoft call log | J | √ |
| User access level | J | √ |
| IPUI registration | √ | √ |
| XML browser | √ | √ |
| Shared Call Appearance (SCA) | √ | √ |
| DECT encryption | | √ |
| Transport Layer Security (TLS) | TLS 1.0/1.1/1.2 | TLS 1.0/1.1/1.2 |
| SRTP Support (Media) | √ | √ |
| Compatibility | · | |
| BroadSoft | √ | J |
| 3CX | | · . |



Yealink Management Cloud Service

The Yealink Device Management Platform offers comprehensive management control and tracking on Yealink video and voice communication endpoints. It delivers a host of capabilities and integrated functionality to efficiently reduce the cost of operation and maintenance.

- · Comprehensive tool set for deployment, management and troubleshooting for up to 20,000 devices
- · Web-based intuitive user interface
- · Scheduling tasks at pre-defined times or after specified time intervals
- Real-time feedback: operation statistics, quality analysis and alarm notifications
- · GDPR security compliance





The Yealink Management Cloud Service (YMCS) mitigates the complexities of pre-provisioning, management, call quality control and troubleshooting. The solution allows system-wide oversight and has the ability to drill down into specific needs for various regions, user groups or even a particular device model.


Benefit Highlights:

- · Based on the Cloud
- · Totally Automatic
- · Powerful Management Capabilities
- · Real time Alarm and Diagnoses
- · Strict Security Strategy

Yealink Management Cloud Service

Cloud-Based, Zero Touch Provisioning & Mgmt





Yealink IP Phone Accessories

Yealink IP Phone accessories range from expansion modules to USB dongles and professional headsets. They increase the usability, impact of your existing collaboration network, and maximize the compatibility of the solutions.





LCD Color-screen Expansion Module EXP50

- · 4.3" 272x480-pixel color screen
- · Color icons for rich visual experience
- · 20 physical keys on each page with dual-color LED
- · 3 control keys with LED for fast switching pages
- · Support up to 3 daisy-chained modules
- · Support Yealink T5 Series only



LCD Expansion Module **EXP43**

- · 4.3" 272x480-pixel color screen
- · Color icons for rich visual experience
- · 20 physical keys on each page with dual-color LEDs
- · Three independent control keys with illuminated LED for fast switching pages
- · Support up to 3 modules daily-chain
- · Support T43U/T46U



DECT Repeater RT30

- · Compatible with DECT CAT-iq 2.0
- · Support Yealink W60B DECT base station
- · Up to 6 repeaters per base station
- · Wall mountable



DECT USB Dongle DD10K

- · Supports Yealink T5 series.
- · Reliable Connection
- · Ease-of-use
- · Plug and Play
- · High Transmission Rate



HD Camera CAM50

- · Support Yealink SIP-T58V/SIP-T58A
- · 2 mega-pixel HD camera with privacy shutter
- · 720p@30fps



Dual Band Wi-Fi USB Dongle WF50

- · Compatible with Yealink T48S/T46S/T42S/T41S/
- · T27G (Version 84)
- · Dual-band connectivity
- · High transmission rate
- · Interference free, reliable connection



Wi-Fi USB Dongle WF40

- · High transmission rate, reliable connection
- · Compliant with IEEE802.11b/g/n
- · Low power consumption
- · Support T27G,T29G, T46G, T48G, T4S series



Bluetooth USB Dongle BT41

- · Support for up to 10 meters of range
- · Compatible with v4.0+HS system
- · Support T27G, T29G, T46G, T48G, T4S Series
- · Wideband audio support



Headset Adapter EHS40

- · Compatible with Jabra, Plantronics, Sennheiser
- · Control call through wireless headset
- · Plug and play
- · Easy to use

