
Yealink

Yealink DECT IP Phone

- High-performance SIP cordless phone system
- 1.8" 128 x 160 TFT color screen with intuitive user interface
- Ruggedized DECT handset with IP54 protection rating
- Up to 20 simultaneous calls
- Up to 10 DECT cordless handsets
- Up to 10 SIP accounts
- Noise Reduction System
- FNR (Flexible Noise Reduction)/Noise Cancellation
- Up to 40-hour talk time
- Up to 575-hour standby time
- Quick charge: 10-minute charging time for 2-hour talk time
- TLS and SRTP security encryption
- Vibration alarm guarantees you not to miss any call even in noisy situations
- Wall mountable charger



Centralized Deployment Quick Charge V



OTA Upgrade

Long Standby Time

The Yealink W77P, a high-performance ruggedized SIP cordless phone system that can register 10 Yealink DECT W57R handsets, is the ideal solution for stressful situations. It features more functions, lines, and mobility. It supports up to 10 SIP accounts and 20 simultaneous calls, improving signal strength and responsiveness to provide a stable and good experience for your mobile communications. What's more, W57R can secure itself from a fall of up to 3.5 meters, water splash in any direction, and dust ingress. Thanks to the vibration alarm, you are guaranteed not to miss any calls, even in noisy and stressful situations.

You can enjoy crystal-clear voice calls because of the new Noise Cancellation technology. W77P consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions. It brings seamless call management for you by combining DECT technology with SIP capabilities, and you can also talk on the phone while walking. You can enjoy the convenience of wireless communication anytime, anywhere, and the extensive benefits and rich features of IP voice phones.

The Yealink DECT IP Phone W77P supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings. This makes it simple to deploy and easy to maintain and upgrade, saving even more time and IT costs for businesses.

- Up to 10 DECT cordless handsets and 10
 SIP accounts
- Up to 20 simultaneous calls to ensure that each handset can make two calls
- Maximum DECT radio coverage: 50 meters
 indoors, 300 meters outdoors
- Energy-saving ECO features

DECT technology:

Yealink DECT technology focuses on highquality Audio VoIP (wideband), and low bitrate data applications. However, we are not compatible with any third-party DECT devices (base station, handset, etc.).

W77P



Yealink

Specifications

Phone Features

- · Up to 20 simultaneous calls
- Up to 10 handsets
- Up to 10 SIP accounts
- · Up to 2 simultaneous calls per handset
- Up to 6 repeaters per base station (RT30)
- Vibration alarm
- Alarm functions: push-button
- · Handset selection for receiving call
- Handset and number selection for placing call
- · Paging, intercom, auto answer, dial plan
- Call hold, call transfer, 3-way conference
- Switching between calls
- Call waiting, mute, silence, DND
- · Caller ID with name and number
- Anonymous call/Anonymous call rejection
- Call forward: Always/Busy/No Answer
- Speed dial/Voicemail/Redial
- Message Waiting Indication (MWI)
- Music on hold (server-based)
- Local phonebook for up to 1000 entries (store in the base)
- Remote phonebook/LDAP/XML phonebook
- Phonebook search/import/export
- 100 call history per handset: All/Placed/Missed/ Received
- Direct IP call without SIP proxy
- Reset to factory, reboot
- · Keypad lock, emergency call
- Broadsoft directory, BroadSoft call log
- · Broadworks feature key synchronization
- Shared Call Appearance (SCA)
- XML browser
- Action URI

Personalization

- 9 ringer melodies
- Screen saver
- Multilingual user interface

Management

Compliance

- Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- Auto-provision with PnP
- Handset upgrade: OTA (Over-The-Air)/ No Perception Upgrade

CE FC 🖉 REACH ISO 9001 💩 🙆 🐬 broadsoft 3CX. Asterisk^o metaswitch

YEALINK NETWORK TECHNOLOGY CO., LTD.

- Configuration: browser/phone/auto-provision
- Trace package and system log export

Audio Features

- Full-duplex speakerphone
- Hearing Aid Compatibility (HAC) compliant
- FNR (Flexible Noise Reduction)/Noise Cancellation
- Receiver volume control: 5 steps
- Ringer volume control: 5 steps+off
- · Multiple advisory tones
- · Acoustic warning for low battery status
- DTMF
- Wideband codec: AMR-WB (optional), G.722
- Narrowband codec: PCMU, PCMA, G.726, G.729, G.729A, iLBC
- VAD, CNG, AGC, PLC, AJB
- AEC
- Support VQ-RTCPXR (RFC6035), RTCP-XR

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SNTP/NTP
- VLAN (802.1Q and 802.1P)
- 802.1x, LLDP
- STUN Client (NAT Traversal)
- UDP/TCP/TLS
- · IP assignment: Static/DHCP
- Support outbound proxy server backup

Security

- Open VPN
- Transport Layer Security (TLS)
- HTTPS (server/client), SRTP (RFC3711)
- Digest authentication
- Secure configuration file via AES encryption
- Support SHA256/SHA512/SHA384
- Three-level configuration mode: Admin/Var/User

DECT

 Frequency bands: 1880–1900 MHz (Europe), 1920–1930 MHz (US) 1902 – 1906 MHz (TH), 1910 – 1920 MHz (BR)

Interface

- 1 x RJ45 10/100 M Ethernet port
- Power over Ethernet (IEEE 802.3af), Class 1

Physical Features

Indoor Range: 50 meters (in ideal conditions)

Outdoor Range: 300 meters (in ideal conditions)

- Battery: 1460 mAh, Lithium-ion, 3.7 V, 5.4 WH
- Up to 40-hour of talk time
- Up to 575-hour of standby time
- 1.8" 128 x 160-pixel TFT color display
- · Desktop or wall mountable
- · LCD backlight, key backlight
- · Energy-saving ECO mode/ECO Mode+
- · Backlit keypad with 25 keys:
- Standard ITU telephone keypad, 12 keys, 4 x 3, with star and pound/hash key
- 5 navigation keys (left, right, up, down, OK)
- 2 softkeys
- 6 function keys (Speaker, message, Off-hook, Cancel, TRAN, Mute)

AC 100-240V Input and DC 5V/600mA Output

Base station size: 130 mm x 100 mm x 25.1 mm

Handset operating temperature: 0 to 40°C (+32-

Handset/Base station storage temperature: -30

Base station operating temperature: -10 to +45

· Color: Handset: Black ; Base: Classic Grey

Handset size: 157 mm x 51 mm x 24 mm

- 3 side keys (volume up/down, alarm)
- 6 shortcut keys
- Three LED indicators on W70B:
 - 1 x Registration LED
 - 1 x Network Status LED
 1 x Power Indicator LED

· External Yealink AC adapter:

Operating humidity: 10%-95%

- W57R Handset with Belt Clip

to 70°C (-22-158°F)

°C (+14 to 113 °F)

Package Features

- Base Stand

Charger Cradle
 Two Power Adapters

- Ethernet Cable

- Decorative Cover

- Quick Start Guide

Qty/CNT: 10 PCS

N.W: 7.456 Kg

• G.W: 8.136 Kg

Email: sales@yealink.com

- Rechargeable Battery

Giftbox size: 205 mm × 182 mm × 95 mm

Carton meas: 502 mm × 378 mm × 215 mm

Web: www.yealink.com

· Package contents:

- W70B Base Station

104°F)



About Yealink

Yealink (Stock Code: 300628) is a global-leading provider of Unified Communication & Collaboration Solutions specialized in video conferencing, voice communications, and collaboration, dedicated to helping every person and organization embrace the power of "Easy Collaboration, High Productivity".

With best-in-class quality, innovative technology, and user-friendly experiences, Yealink is one of the best providers in more than 140 countries and regions, ranks No.1 in the global market share of IP Phone, and is the Top 5 leader in the video conferencing market (Frost & Sullivan, 2021).

For more information about Yealink, click here.

Copyright

Copyright © 2023 YEALINK (XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD. Web: www.yealink.com Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District, Xiamen, Fujian, P.R.C Copyright©2023 Yealink Inc. All right reserved.